

## Dome Fiber Optic Splice Closure

### CV003

#### Description:

CV003 provide 6 fiber cable in-out round ports for the diameter  $\Phi 7$ - $\Phi 18$ mm optical cable in and out. It is used for splicing and protecting optical cables.

This product is made of ABS and sealed by silicon rubber and mechanical sealing structure filled with the sealing material. The external component and fastening piece are all made of the high-quality iron. It can be opened after sealing.



#### Application:

Aerial -hanger, Wall-mounting, Pole mounted

#### Specification:

|                                  |   |
|----------------------------------|---|
| Dimension / Weight               | $\Phi 170.5 \times 441$ mm / 1.8Kg            |
| Cable diameter                   | $\Phi 7$ - $\Phi 18$ mm                       |
| Cable entry ports                | 3 in & 3 out                                  |
| Max. splice tray / Max. Capacity | 5 (12core/tray, 24core/tray duplex) / 120core |
| Cable port sealing structure     | Sealing rubber & Nut lock                     |
| Closure sealing structure        | Mechanical sealing                            |
| Water proof grade                | IP67  |
| Packing size(cm) / Weight        | 62*47*41(6PCS) / 17Kg(6PCS)                   |

#### Components:

- Splice protector sleeve(60mm)
- Sticky cincture:1 pc
- Sealing washer(rubber):1 pc
- Plug for cable port (rubber):6 pcs
- Hanging hook:1 set

